

531,027
10/531,027

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 April 2004 (29.04.2004)

PCT

(10) International Publication Number
WO 2004/036920 A1

(51) International Patent Classification⁷: **H04N 7/50, 7/36**

(21) International Application Number:
PCT/IB2003/004522

(22) International Filing Date: 13 October 2003 (13.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02292552.3 16 October 2002 (16.10.2002) EP

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **DRIEUX, Marc**

[FR/FR]; 156 Boulevard Haussmann, F-75008 Paris (FR).
GROLIERE, Françoise [FR/FR]; 156 Boulevard Haussmann, F-75008 Paris (FR). **SNOOK, Daniel** [GB/FR];
156 Boulevard Haussmann, F-75008 Paris (FR).


(74) Agent: **LANDOUSY, Christian**; Société Civile SPID,
156 Boulevard Haussmann, F-75008 Paris (FR).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: VIDEO ENCODING METHOD



(57) Abstract: The present invention relates to an encoding method processing video object planes (VOPs) of I, P or B type and including a dynamic allocation of said VOPs. According to said method, for each input frame a preliminary forward motion estimation is carried out between current and previous frames. Current and previous motion fields are then used to evaluate a coherence factor, expressed as connected to the sums of local differences within current and previous motion field. According to the value of the coherence factor with respect to an empirically determined threshold, a decision is finally taken on the type of the frame to be coded.

WO 2004/036920 A1